

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

1 Identification

- **Product Name:** RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B
- **Product Number:** 194-R0-101
- **Manufacturer/Supplier:**
Harrison Paint Company
1329 Harrison Ave SW
Canton, OH 44706
USA
- **Information telephone number:** 330-455-5125
- **Emergency telephone number:** 330-455-5125

2 Hazard(s) identification

- **Classification of the substance or mixture:**
Eye Damage 1 H318 Causes serious eye damage.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
Germ Cell Mutagenicity 1B H340 May cause genetic defects.
Carcinogenicity 1B H350 May cause cancer.
Toxic to Reproduction 1B H360 May damage fertility or the unborn child.
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS05 GHS07 GHS08

- **Signal word:** Danger
- **Hazard-determining components of labeling:**
3-Oxazolidineethanol, 2-(1-methylethyl)-, 3,3'-carbonate
Solvent naphtha (petroleum), light arom.
dibutyltin dilaurate
- **Hazard statements:**
Causes serious eye damage.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May damage fertility or the unborn child.
- **Precautionary statements:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a doctor.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B

(Contd. from page 1)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:
NFPA ratings (scale 0 - 4)


Health = 3

Fire = 1

Reactivity = 0

HMIS-ratings (scale 0 - 4)


Health = *3

Fire = 1

Reactivity = 0

Other hazards:
Results of PBT and vPvB assessment:
PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixture
Description: Mixture of the substances listed below with nonhazardous additions.

Hazardous components:

108-32-7	propylene carbonate	40-60%
145899-78-1	3-Oxazolidineethanol, 2-(1-methylethyl)-, 3,3'-carbonate	5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-5%
123-54-6	pentane-2,4-dione	≤1%
77-58-7	dibutyltin dilaurate	≥0.1-≤0.5%

4 First-aid measures

Description of first aid measures:
For inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

For skin contact: Immediately wash with water and soap and rinse thoroughly.

For eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

For swallowing:

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

Information for doctor:
Most important symptoms and effects, both acute and delayed: No further relevant information available.

Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B

(Contd. from page 2)

5 Fire-fighting measures

- **Extinguishing media:**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture:** No further relevant information available.
- **Advice for firefighters:**
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures:**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, universal binder or other inert absorbent).
Use neutralizing agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

108-32-7	propylene carbonate	34 mg/m ³
123-54-6	pentane-2,4-dione	75 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
108-83-8	2,6-dimethylheptan-4-one	75 ppm
98-82-8	Cumene	50 ppm

· PAC-2:

108-32-7	propylene carbonate	370 mg/m ³
123-54-6	pentane-2,4-dione	110 ppm
77-58-7	dibutyltin dilaurate	8 mg/m ³
108-83-8	2,6-dimethylheptan-4-one	330 ppm
98-82-8	Cumene	300 ppm

· PAC-3:

108-32-7	propylene carbonate	2,200 mg/m ³
123-54-6	pentane-2,4-dione	200 ppm
77-58-7	dibutyltin dilaurate	48 mg/m ³
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
98-82-8	Cumene	730 ppm

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B

(Contd. from page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling:**
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
 - Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities:**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s):** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with limit values that require monitoring at the workplace:**
 - The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
 - At this time, the other constituents have no known exposure limits.

123-54-6 pentane-2,4-dione

TLV	Long-term value: 25 ppm
	Skin

77-58-7 dibutyltin dilaurate

PEL	Long-term value: 0.1 mg/m ³
	as Sn

REL	Long-term value: 0.1 mg/m ³
	as Sn, Skin

TLV	Short-term value: 0.2 mg/m ³
	Long-term value: 0.1 mg/m ³
	as Sn; A4; Skin

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls:**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before eating, smoking, using the restroom and at the end of the workday.
 - Store protective clothing separately.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- **Breathing equipment:**
 - In case of brief exposure or low concentrations, use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B

(Contd. from page 4)

Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties:
General Information:
Appearance:

Form:	Liquid
Color:	Amber
Odor:	Sweetish
Odor threshold:	Not determined.

pH-value: Not determined.

Change in condition:

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	242 °C (467.6 °F)

Flash point: 135 °C (275 °F)

Flammability (solid, gaseous): Not applicable.

Auto igniting: 430 °C (806 °F)

Decomposition temperature: Not determined.

Ignition temperature: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

Vapor pressure at 20 °C (68 °F): 0 hPa

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B

(Contd. from page 5)

· Density at 20 °C (68 °F):	1.14 g/cm ³ (9.513 lbs/gal)
· Relative density:	Not determined.
· Vapour density:	Heavier than air.
· Evaporation rate:	Slower than ether.
· Solubility in / Miscibility with:	
Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	49.5 %
VOC content:	2.85 %
	58.1 g/l / 0.48 lb/gal
Solids content:	50.1 %
· Other information:	No further relevant information available.

10 Stability and reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Do not store or use near sparks, flame, or other ignition sources.
- **Incompatible materials:** Strong acids and alkalis, bleach, strong oxidizers.
- **Hazardous decomposition products:**
Burning may yield carbon monoxide, carbon dioxide, oxides of nitrogen, and various hydrocarbons.

11 Toxicological information

- **Information on toxicological effects:**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B

(Contd. from page 6)

· Carcinogenic categories:
· IARC (International Agency for Research on Cancer):

98-82-8	Cumene	2B
---------	--------	----

· NTP (National Toxicology Program):

98-82-8	Cumene	R
---------	--------	---

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients is listed.

12 Ecological information

· Toxicity:
· Aquatic toxicity: No further relevant information available.

· Persistence and degradability: No further relevant information available.

· Behavior in environmental systems:
· Bioaccumulative potential: No further relevant information available.

· Mobility in soil: No further relevant information available.

· Additional ecological information:
· General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

· Results of PBT and vPvB assessment:
· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects: No further relevant information available.

13 Disposal considerations

· Waste treatment methods:
· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:
· Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number:
· DOT, IMDG, IATA Not Regulated

· UN proper shipping name:
· DOT, IMDG, IATA Not Regulated

· Transport hazard class(es):
· DOT, ADN, IMDG, IATA
· Class Not Regulated

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B

(Contd. from page 7)

· Packing group:	
· DOT, IMDG, IATA	Not Regulated
· Environmental hazards:	Not applicable.
· Special precautions for user:	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not applicable.
· UN "Model Regulation":	Not Regulated

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture:

· SARA:

 · **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

 · **Section 313 (Specific toxic chemical listings):**

98-82-8 | Cumene

 · **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

 · **Hazardous Air Pollutants**

98-82-8 | Cumene

 · **Proposition 65:**

 · **Chemicals known to cause cancer:**

98-82-8 | Cumene

 · **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

 · **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

 · **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

 · **Carcinogenic categories:**

 · **EPA (Environmental Protection Agency)**

98-82-8 | Cumene

D, CBD

 · **TLV (Threshold Limit Value)**

77-58-7 | dibutyltin dilaurate

A4

 · **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

 · **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B*(Contd. from page 8)***Hazard pictograms:**

GHS05 GHS07 GHS08

Signal word: Danger**Hazard-determining components of labeling:**

3-Oxazolidineethanol, 2-(1-methylethyl)-, 3,3'-carbonate
Solvent naphtha (petroleum), light arom.
dibutyltin dilaurate

Hazard statements:

Causes serious eye damage.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May damage fertility or the unborn child.

Precautionary statements:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a doctor.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:**Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Laboratory**Contact:** Laboratory Manager**Date of preparation / last revision:** 11/12/2025**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/05/2025

Product Name: RR-8000 ALIPHATIC HW URETHANE TOPCOAT PT B*(Contd. from page 9)*

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Eye Damage 1: Serious eye damage/eye irritation – Category 1
Sensitization - Skin 1: Skin sensitisation – Category 1
Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B
Carcinogenicity 1B: Carcinogenicity – Category 1B
Toxic to Reproduction 1B: Reproductive toxicity – Category 1B

US