

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

1 Identification

- **Product Name:** RR-3000 EPOXY UV GROUT COAT PT A
- **Product Number:** 194-M9-103
- **Manufacturer/Supplier:**
Harrison Paint Company
1329 Harrison Ave SW
Canton, OH 44706
USA
- **Information telephone number:** 330-455-5125
- **Emergency telephone number:** 330-455-5125

2 Hazard(s) identification

- **Classification of the substance or mixture:**
Skin Irritation 2 H315 Causes skin irritation.
Eye Irritation 2A H319 Causes serious eye irritation.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS07

- **Signal word:** Warning
- **Hazard-determining components of labeling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
1,4-bis(2,3-epoxypropoxy)butane
- **Hazard statements:**
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
- **Precautionary statements:**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves / eye protection / face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Specific treatment (see on this label).
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 1
Reactivity = 0

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A

(Contd. from page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· Other hazards:
· Results of PBT and vPvB assessment:

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixture
· Description: Mixture of the substances listed below with nonhazardous additions.

· Hazardous components:

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	60-80%
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	≥ 5 -<10%
100-51-6	Benzyl alcohol	5-10%
67762-90-7	Silicon Dioxide	2.5-5%
108-94-1	cyclohexanone	2.5-5%
64741-65-7	Naphtha (petroleum), heavy alkylate	1-2.5%

4 First-aid measures

· Description of first aid measures:
· General information: Immediately remove any clothing soiled by the product.

· For inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· For skin contact: Immediately wash with water and soap and rinse thoroughly.

· For eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· For swallowing:

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Information for doctor:
· Most important symptoms and effects, both acute and delayed: No further relevant information available.

· Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media:
· Suitable extinguishing agents: Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture: No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A

(Contd. from page 2)

- **Advice for firefighters:**
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures:** Not required.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, universal binder or other inert absorbent).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

PAC-1:

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	90 mg/m ³
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	16 mg/m ³
100-51-6	Benzyl alcohol	30 ppm
67762-90-7	Silicon Dioxide	120 mg/m ³
108-94-1	cyclohexanone	60 ppm

PAC-2:

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	990 mg/m ³
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	170 mg/m ³
100-51-6	Benzyl alcohol	52 ppm
67762-90-7	Silicon Dioxide	1,300 mg/m ³
108-94-1	cyclohexanone	830 ppm

PAC-3:

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	5,900 mg/m ³
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	220 mg/m ³
100-51-6	Benzyl alcohol	740 ppm
67762-90-7	Silicon Dioxide	7,900 mg/m ³
108-94-1	cyclohexanone	5000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A*(Contd. from page 3)*

- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities:**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s):** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters:**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

100-51-6 Benzyl alcohol

WEEL Long-term value: 10 ppm

67762-90-7 Silicon Dioxide

PEL Long-term value: 6, 15*, 5** mg/m³
*Total Dust, **Respirable Fraction

108-94-1 cyclohexanone

PEL Long-term value: 200 mg/m³, 50 ppmREL Long-term value: 100 mg/m³, 25 ppm
SkinTLV Short-term value: 50 ppm
Long-term value: 20 ppm
Skin, BEI, A3

- **Ingredients with biological limit values:**

108-94-1 cyclohexanone

BEI 80 mg/L
Medium: urine
Time: end of shift at end of workweek
Parameter: 1,2-Cyclohexanediol (with hydrolysis, nonspecific, nonquantitative)8 mg/L
Medium: urine
Time: end of shift
Parameter: Cyclohexanol (with hydrolysis, nonspecific, nonquantitative)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls:**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before eating, smoking, using the restroom and at the end of the workday.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A

(Contd. from page 4)

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low concentrations, use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material:**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties:**

- **General Information:**

- **Appearance:**

· Form:	Gel
· Color:	Opaque
· Odor:	Nearly odorless
· Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition:**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	114-118 °C (237.2-244.4 °F)

- **Flash point:** 101 °C (213.8 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Auto igniting:** 435 °C (815 °F)

- **Decomposition temperature:** Not determined.

- **Ignition temperature:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A

(Contd. from page 5)

· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.15 g/cm ³ (9.597 lbs/gal)
· Relative density:	Not determined.
· Vapour density:	Heavier than air.
· Evaporation rate:	Slower than ether.
· Solubility in / Miscibility with:	
Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	4.7 %
VOC content:	4.67 %
	53.7 g/l / 0.45 lb/gal
Solids content:	98.0 %
· Other information:	No further relevant information available.

10 Stability and reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Do not store or use near sparks, flame, or other ignition sources.
- **Incompatible materials:** Strong acids and alkalis, bleach, strong oxidizers.
- **Hazardous decomposition products:**
Burning may yield carbon monoxide, carbon dioxide, oxides of nitrogen, and various hydrocarbons.

11 Toxicological information

- **Information on toxicological effects:**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
100-51-6 Benzyl alcohol		
Oral	LD50	1,230 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A

(Contd. from page 6)

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

Carcinogenic categories:
IARC (International Agency for Research on Cancer):

108-94-1	cyclohexanone	3
----------	---------------	---

NTP (National Toxicology Program):

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients is listed.

12 Ecological information

Toxicity:

- Aquatic toxicity:** No further relevant information available.

- Persistence and degradability:** No further relevant information available.

Behavior in environmental systems:

- Bioaccumulative potential:** No further relevant information available.

- Mobility in soil:** No further relevant information available.

Additional ecological information:
General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment:

- PBT:** Not applicable.

- vPvB:** Not applicable.

- Other adverse effects:** No further relevant information available.

13 Disposal considerations

Waste treatment methods:
Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

- Recommendation:** Disposal must be made according to official regulations.

- Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

UN-Number:

- DOT** Not Regulated

- IMDG, IATA** UN3082

UN proper shipping name:

- DOT** Not Regulated

- IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (reaction product: bisphenol-A-

(Contd. on page 8)

Safety Data Sheet


acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A

(Contd. from page 7)

· IATA	(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
· Transport hazard class(es):	
· DOT	
· Class	Not Regulated
· IMDG, IATA	
	
· Class	9 Miscellaneous dangerous substances and articles
· Label	9
· Packing group:	
· DOT	Not Regulated
· IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· Special precautions for user:	Warning: Miscellaneous dangerous substances and articles
· Hazard identification number (Kemler code):	90
· EMS Number:	F-A,S-F
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:	Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ):	5L
· Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture:
No further relevant information available.

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A

(Contd. from page 8)

· **SARA:**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)	ACTIVE
2425-79-8	1,4-bis(2,3-epoxypropoxy)butane	ACTIVE
100-51-6	Benzyl alcohol	ACTIVE
67762-90-7	Silicon Dioxide	ACTIVE
108-94-1	cyclohexanone	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65:**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories:**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

108-94-1	cyclohexanone	A3
----------	---------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS07

· **Signal word:** Warning

· **Hazard-determining components of labeling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

1,4-bis(2,3-epoxypropoxy)butane

· **Hazard statements:**

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/12/2025

Product Name: RR-3000 EPOXY UV GROUT COAT PT A*(Contd. from page 9)*

May cause an allergic skin reaction.

Precautionary statements:

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Laboratory· **Contact:** Laboratory Manager· **Date of preparation / last revision:** 11/12/2025**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1