

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

1 Identification

- **Product Name:** RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A
- **Product Number:** 194-M0-100
- **Manufacturer/Supplier:**
Harrison Paint Company
1329 Harrison Ave SW
Canton, OH 44706
USA
- **Information telephone number:** 330-455-5125
- **Emergency telephone number:** 330-455-5125

2 Hazard(s) identification

- **Classification of the substance or mixture:**
Skin Irritation 2 H315 Causes skin irritation.
Eye Irritation 2A H319 Causes serious eye irritation.
Sensitization - Skin 1 H317 May cause an allergic skin reaction.
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS07

- **Signal word:** Warning
- **Hazard-determining components of labeling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
- **Hazard statements:**
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
- **Precautionary statements:**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves / eye protection / face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Specific treatment (see on this label).
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 1
Reactivity = 0

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

Product Name: RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A

(Contd. from page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· Other hazards:
· Results of PBT and vPvB assessment:
· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixture
· Description: Mixture of the substances listed below with nonhazardous additions.

· Hazardous components:

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	80-100%
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	10-20%

4 First-aid measures

· Description of first aid measures:
· General information: Immediately remove any clothing soiled by the product.

· For inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· For skin contact: Immediately wash with water and soap and rinse thoroughly.

· For eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· For swallowing:

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Information for doctor:
· Most important symptoms and effects, both acute and delayed: No further relevant information available.

· Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media:
· Suitable extinguishing agents: Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture: No further relevant information available.

· Advice for firefighters:
· Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures: Not required.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

Product Name: RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A

(Contd. from page 2)

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, universal binder or other inert absorbent).
 Dispose contaminated material as waste according to section 13.
 Ensure adequate ventilation.

Reference to other sections:

See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

Protective Action Criteria for Chemicals
PAC-1:

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	90 mg/m ³
------------	--	----------------------

PAC-2:

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	990 mg/m ³
------------	--	-----------------------

PAC-3:

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	5,900 mg/m ³
------------	--	-------------------------

7 Handling and storage

Handling:
Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities:
Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.

Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see section 7.

Control parameters:
Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls:
Personal protective equipment:
General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

Product Name: RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A

(Contd. from page 3)

Wash hands before eating, smoking, using the restroom and at the end of the workday.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low concentrations, use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves:**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material:**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties:**

· **General Information:**

· **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Nearly odorless
Odor threshold:	Not determined.

· **pH-value:** Not applicable.

· **Change in condition:**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	114-118 °C (237.2-244.4 °F)

· **Flash point:** 266 °C (510.8 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

Product Name: RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A

(Contd. from page 4)

· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.12 g/cm ³ (9.346 lbs/gal)
· Relative density:	Not determined.
· Vapour density:	Heavier than air.
· Evaporation rate:	Slower than ether.
· Solubility in / Miscibility with:	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
Solids content:	100.0 %
· Other information:	No further relevant information available.

10 Stability and reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** Do not store or use near sparks, flame, or other ignition sources.
- **Incompatible materials:** Strong acids and alkalis, bleach, strong oxidizers.
- **Hazardous decomposition products:**
Burning may yield carbon monoxide, carbon dioxide, oxides of nitrogen, and various hydrocarbons.

11 Toxicological information

- **Information on toxicological effects:**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

Product Name: RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A

(Contd. from page 5)

· Carcinogenic categories:
· IARC (International Agency for Research on Cancer):

None of the ingredients is listed.

· NTP (National Toxicology Program):

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients is listed.

12 Ecological information

· Toxicity:
· Aquatic toxicity: No further relevant information available.

· Persistence and degradability: No further relevant information available.

· Behavior in environmental systems:
· Bioaccumulative potential: No further relevant information available.

· Mobility in soil: No further relevant information available.

· Additional ecological information:
· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment:
· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects: No further relevant information available.

13 Disposal considerations

· Waste treatment methods:
· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:
· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number:
· DOT

Not Regulated

· IMDG, IATA

UN3082

· UN proper shipping name:
· DOT

Not Regulated

· IMDG, IATA

 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
 LIQUID, N.O.S. (reaction product: bisphenol-A-
 (epichlorhydrin) epoxy resin (number average molecular weight
 ≤ 700))

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

Product Name: RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A

(Contd. from page 6)

· Transport hazard class(es):
· DOT
· Class

Not Regulated

· IMDG, IATA

· Class

9 Miscellaneous dangerous substances and articles

· Label

9

· Packing group:
· DOT

Not Regulated

· IMDG, IATA

III

· Environmental hazards:
· Marine pollutant:

Symbol (fish and tree)

· Special marking (IATA):

Symbol (fish and tree)

· Special precautions for user:

Warning: Miscellaneous dangerous substances and articles

· Hazard identification number (Kemler code):

90

· EMS Number:

F-A,S-F

· Stowage Category

A

· Transport in bulk according to Annex II of MARPOL/73/78 and the IBC Code:

Not applicable.

· Transport/Additional information:
· IMDG
· Limited quantities (LQ):

5L

· Excepted quantities (EQ):

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

 UN 3082 ENVIRONMENTALLY HAZARDOUS
 SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT:
 BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN
 (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture:

No further relevant information available.

· SARA:
· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

Product Name: RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A

(Contd. from page 7)

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65:
· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories:
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:


GHS07

· Signal word: Warning

· Hazard-determining components of labeling:

 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

· Hazard statements:

 Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.

· Precautionary statements:

 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves / eye protection / face protection.
 If on skin: Wash with plenty of water.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 Specific treatment (see on this label).
 If eye irritation persists: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date: 11/12/2025

Revised on: 11/04/2025

Product Name: RR-1000 EPOXY MOISTURE VAPOR BARRIER PT A· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. from page 8)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Laboratory
- **Contact:** Laboratory Manager
- **Date of preparation / last revision:** 11/12/2025
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - Skin Irritation 2: Skin corrosion/irritation – Category 2
 - Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
 - Sensitization - Skin 1: Skin sensitisation – Category 1

US